

VF 600/60 R 30 NRO 162D TL TRAXION OPTIMALL

EAN CODE: **8714692362262**
SKU CODE: **LB60603062DTOLA00**
ECE NUMBER: **E4-106R-004137**



Recommended rim width:	DW20B
Permitted rim width:	DW21B
NRO rim width:	DW18L
Nominal Tyre Pressure:	200 kpa
Section Width:	600 mm
Outer Diameter:	1480 mm
Static Loaded Radius:	655 mm
Rolling Circumference:	4390 mm
SRI:	700
Tread depth:	48 mm

Speed (km/h)	Pressure (bar)									
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40
10L	2650	3060	3445	3855	4260	4815	5055	5445	5650	5940
10H	2495	2915	3330	3745	4160	4590	4840	5130		
25	2520	2940	3360	3780	4200	4635	4885	5180		
30	2495	2915	3330	3745	4160	4590	4840	5130		
40	2425	2830	3235	3640	4045	4465	4705	4990		
50	2380	2780	3175	3570	3970	4380	4620	4895		
65	2310	2695	3080	3470	3855	4250	4485	4750		
70	2105	2455	2805	3155	3505	3870	4080	4325		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.