

VF 710/60 R 38 NRO 174D TL TRAXION OPTIMALL

EAN CODE: **8714692805677**
 SKU CODE: **LB71603874DTOLA00**
 ECE NUMBER: **E4-106R-004700**



Recommended rim width:	DW25B
NRO rim width:	DW23B
Nominal Tyre Pressure:	200 kpa
Section Width:	725 mm
Outer Diameter:	1840 mm
Static Loaded Radius:	810 mm
Rolling Circumference:	5430 mm
SRI:	875
Tread depth:	57 mm

Speed (km/h)	Pressure (bar)									
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40
10L	3825	4420	4975	5565	6155	6955	7305	7865	8160	8375
10H	3605	4210	4810	5410	6010	6640	6995	7235		
25	3640	4245	4855	5460	6065	6705	7060	7305		
30	3605	4210	4810	5410	6010	6640	6995	7235		
40	3505	4090	4675	5260	5845	6460	6800	7035		
50	3440	4015	4585	5160	5735	6335	6670	6900		
65	3340	3895	4455	5010	5565	6150	6475	6700		
70	3040	3545	4050	4560	5065	5595	5895	6095		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.