

VF 710/60 R 42 NRO 176D TL TRAXION OPTIMALL

EAN CODE: **8714692362286**
SKU CODE: **LB71604276DTOLA00**
ECE NUMBER: **E4-106R-004138**



Recommended rim width:	DW25B
NRO rim width:	DW23B
Nominal Tyre Pressure:	200 kpa
Section Width:	730 mm
Outer Diameter:	1925 mm
Static Loaded Radius:	850 mm
Rolling Circumference:	5710 mm
SRI:	925
Tread depth:	57 mm

Speed (km/h)	Pressure (bar)									
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40
10L	4010	4630	5215	5835	6455	7290	7655	8240	8555	8875
10H	3780	4410	5040	5670	6300	7020	7330	7670		
25	3815	4450	5085	5725	6360	7085	7400	7740		
30	3780	4410	5040	5670	6300	7020	7330	7670		
40	3675	4290	4900	5515	6125	6825	7130	7455		
50	3605	4205	4805	5410	6010	6695	6990	7315		
65	3500	4085	4665	5250	5835	6500	6790	7100		
70	3185	3715	4245	4780	5310	5915	6175	6460		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES