

VF 600/60 R 28 NRO 160D TL TRAXION OPTIMALL

EAN CODE: **8714692805622**
SKU CODE: **LB60602860DTOLA00**
ECE NUMBER: **E4-106R-004698**



Recommended rim width:	DW20B
Permitted rim width:	DW21B
NRO rim width:	DW18L
Nominal Tyre Pressure:	200 kpa
Section Width:	605 mm
Outer Diameter:	1420 mm
Static Loaded Radius:	605 mm
Rolling Circumference:	4180 mm
SRI:	675
Tread depth:	48 mm

Speed (km/h)	Pressure (bar)									
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40
10L	2570	2965	3340	3735	4135	4670	4905	5275	5480	5625
10H	2420	2825	3230	3630	4035	4455	4695	4860		
25	2445	2850	3255	3665	4070	4495	4740	4905		
30	2420	2825	3230	3630	4035	4455	4695	4860		
40	2355	2745	3140	3530	3920	4330	4565	4725		
50	2310	2695	3080	3465	3850	4250	4475	4635		
65	2240	2615	2990	3360	3735	4125	4345	4500		
70	2040	2380	2720	3060	3400	3755	3955	4095		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES