

VF 540/65 R 28 NRO 154D TL TRAXION OPTIMALL



EAN CODE: **8714692805615**
 SKU CODE: **LB54652854DTOLA00**
 ECE NUMBER: **E4-106R-004781**

Recommended rim width:	DW18L
NRO rim width:	DW16L
Nominal Tyre Pressure:	160 kpa
Section Width:	545 mm
Outer Diameter:	1410 mm
Static Loaded Radius:	620 mm
Rolling Circumference:	4120 mm
SRI:	675
Tread depth:	46 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2410	2785	3135	3510	3880	4230	4605	4810
10H	2275	2650	3030	3410	3790	4050		
25	2295	2675	3060	3440	3825	4090		
30	2275	2650	3030	3410	3790	4050		
40	2210	2580	2945	3315	3685	3940		
50	2170	2530	2890	3250	3615	3865		
65	2105	2455	2805	3155	3510	3750		
70	1915	2235	2555	2875	3190	3415		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.