

# 480/65 R 28 136D TL TRAXION 65

EAN CODE: **8714692360503**  
 SKU CODE: **LB48652836DT6LA00**  
 ECE NUMBER: **E4-106R-003346**



Recommended rim width:	<b>DW15L</b>
Permitted rim width:	<b>(D)W14/W15L</b>
Nominal Tyre Pressure:	<b>160 kpa</b>
Section Width:	<b>485 mm</b>
Outer Diameter:	<b>1350 mm</b>
Static Loaded Radius:	<b>610 mm</b>
Rolling Circumference:	<b>4015 mm</b>
SRI:	<b>650</b>
Tread depth:	<b>42 mm</b>

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1845	2095	2350	2600	2855	3055	3225	3420
10H	1530	1775	2020	2225	2400	2575		
25	1575	1830	2080	2295	2475	2655		
30	1530	1775	2020	2225	2400	2575		
40		1690	1920	2120	2285	2455		
50		1620	1840	2030	2195	2350		
65			1755	1935	2090	2240		
70			1595	1760	1900	2040		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.