

440/65 R 24 128D TL TRAXION 65

EAN CODE: **8714692360466**
 SKU CODE: **LB44652428DT6LA00**
 ECE NUMBER: **E4-106R-003342**



Recommended rim width:	DW14L
Permitted rim width:	(D)W13(L)/ W14L/(D)W15L
Nominal Tyre Pressure:	160 kpa
Section Width:	440 mm
Outer Diameter:	1185 mm
Static Loaded Radius:	540 mm
Rolling Circumference:	3545 mm
SRI:	575
Tread depth:	40 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1505	1705	1915	2120	2325	2490	2625	2785
10H	1245	1445	1645	1815	1955	2070		
25	1285	1490	1695	1870	2015	2135		
30	1245	1445	1645	1815	1955	2070		
40		1375	1565	1725	1865	1970		
50		1320	1500	1655	1785	1890		
65			1430	1575	1700	1800		
70			1300	1435	1550	1640		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.