



Product Data

Transmax Manual EP 80W

Manual Transmission Fluid

Description

Castrol Transmax Manual EP 80W is a synthetic technology based fluid suitable for use in applications where API GL-4 performance is required. Transmax Manual EP 80W is approved for use in MB transmissions used in light commercial vehicles and trucks and also approved for use in ZF manual transmissions.

Advantages

- High thermal stability protects against deposit formation and oil thickening maintaining the life and performance of lubricant and transmission.
- Good antiwear and load carrying characteristics extend the life of components.

Typical Characteristics

Name	Method	Units	Transmax Manual EP 80W
Density @ 15°C, Relative	ASTM D1298	g/ml	0.869
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	10.0
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	79
Viscosity Index	ASTM D2270	None	109
Viscosity, Brookfield @ -26°C (80W)	ASTM D2983	mPa.s (cP)	21500
Pour Point	ASTM D97	°C	-42
Flash Point, COC	ASTM D92	°C	199

Product Performance Claims

API GL-4
DTFR 13B100 (MB 235.1)
MB-Approval 235.14
ZF TE-ML 17A

Additional Information

Transmax Manual EP 80W is registered under the following ZF approval numbers: ZF004862

Transmax Manual EP 80W
24 May 2024
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com