

15.0/55 – 17 IMP 134 A8 TL AW

EAN CODE: **8714692263293**
SKU CODE: **LB155517348AWLA00**
ECE NUMBER: **E4-106R-000420**



Recommended rim width:	13.00
Nominal Tyre Pressure:	260 kpa
Section Width:	385 mm
Outer Diameter:	865 mm
Static Loaded Radius:	390 mm
Rolling Circumference:	2580 mm
SRI:	410
Tread depth:	12 mm

Speed (km/h)	Pressure (bar)							
	1,00	1,25	1,50	1,75	2,00	2,25	2,50	3,50
	LLV							HLV
10	1650	1880	2090	2290	2480	2650	2820	3440
25	1400	1600	1780	1950	2100	2250	2400	2920
30	1320	1500	1670	1830	1980	2120	2260	2750
40			1490	1640	1770	1890	2010	2450
50				1470	1590	1710	1810	2210

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- LLV (Low Load Variation)
- HLV (High Load Variation)