

400/60 - 15.5 IMP 145A8 TL FLOTATION+

EAN CODE: **8714692076787**
 SKU CODE: **LB406015458FLLA00**
 ECE NUMBER: **E4-106R-000392**



Recommended rim width:	AG 13.00
Nominal Tyre Pressure:	360 kpa
Section Width:	410 mm
Outer Diameter:	850 mm
Static Loaded Radius:	380 mm
Rolling Circumference:	2530 mm
SRI:	410
Tread depth:	14 mm

Speed (km/h)	Pressure (bar)								
	1,00	1,40	1,80	2,20	2,60	3,00	3,40	3,60	4,40
	LLV								HLV
10	1550	1940	2320	2710	3100	3480	3880	4060	4840
25	1320	1640	1970	2300	2630	2960	3280	3460	4120
30	1240	1550	1860	2170	2480	2790	3100	3260	3880
40		1380	1660	1940	2210	2490	2760	2900	3460
50			1490	1740	1990	2240	2490	2610	3120

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- LLV (Low Load Variation)
- HLV (High Load Variation)