

500/50 - 17 IMP 149A8 TL FLOTATION+

EAN CODE: **8714692201042**
SKU CODE: **LB505017498FLLA00**
ECE NUMBER: **E4-106R-000399**

Recommended rim width:	16.00
Nominal Tyre Pressure:	280 kpa
Section Width:	500 mm
Outer Diameter:	950 mm
Static Loaded Radius:	430 mm
Rolling Circumference:	2890 mm
SRI:	450
Tread depth:	15 mm



Speed (km/h)	Pressure (bar)										
	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80	3,40
	LLV										HLV
10	2140	2410	2680	2940	3220	3480	3740	4020	4280	4540	5360
25	1820	2050	2270	2500	2730	2960	3180	3420	3640	3860	4540
30	1710	1930	2140	2360	2570	2780	3000	3220	3420	3640	4280
40			1910	2100	2290	2490	2680	2870	3060	3240	3820
50					2060	2240	2410	2580	2750	2920	3440

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- LLV (Low Load Variation)
- HLV (High Load Variation)