

520/50 R 17 IMP 147D TL FLOTATION TRAC

EAN CODE: **8714692291593**
 SKU CODE: **LB52501747DFTLA00**
 ECE NUMBER: **E4-106R-000472**



Recommended rim width:	16.00
Nominal Tyre Pressure:	400 kpa
Section Width:	505 mm
Outer Diameter:	965 mm
Static Loaded Radius:	445 mm
Rolling Circumference:	2970 mm
SRI:	450
Tread depth:	17 mm

Speed (km/h)	Pressure (bar)								
	0,80	1,20	1,60	2,00	2,40	2,80	3,20	3,60	4,00
10	1780	2435	2890	3310	3760	4195	4635	5095	5535
25	1565	2135	2535	2905	3300	3680	4070	4475	4860
30	1495	2045	2425	2775	3155	3520	3890	4275	4645
40	1345	1840	2180	2500	2840	3170	3500	3850	4180
50	1200	1635	1940	2225	2525	2820	3115	3425	3720
65	990	1355	1605	1840	2090	2330	2575	2830	3075
70	900	1230	1460	1675	1900	2120	2345	2575	2800

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.