

520/55 R 22.5 IMP 148D TL FLOTATION TRAC



EAN CODE: **8714692291609**
SKU CODE: **LB52552248DFTLA00**
ECE NUMBER: **E4-106R-000531**

Recommended rim width:	AG 16.00
Nominal Tyre Pressure:	320 kpa
Section Width:	515 mm
Outer Diameter:	1155 mm
Static Loaded Radius:	530 mm
Rolling Circumference:	3560 mm
SRI:	550
Tread depth:	17 mm

Speed (km/h)	Pressure (bar)						
	0,80	1,20	1,60	2,00	2,40	2,80	3,20
10	2190	2995	3550	4070	4625	5155	5670
25	1925	2630	3120	3575	4060	4525	4975
30	1840	2510	2980	3415	3880	4325	4755
40	1655	2260	2685	3075	3495	3895	4285
50	1475	2015	2385	2735	3110	3465	3810
65	1220	1665	1975	2260	2570	2865	3150
70	1110	1515	1795	2060	2335	2605	2865

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.