

540/65 R 24 140D TL TRAXION 65

EAN CODE: **8714692360480**
SKU CODE: **LB54652440DT6LA00**
ECE NUMBER: **E4-106R-003344**



Recommended rim width:	DW16L
Permitted rim width:	W16L/(D)W18L
Nominal Tyre Pressure:	160 kpa
Section Width:	540 mm
Outer Diameter:	1315 mm
Static Loaded Radius:	590 mm
Rolling Circumference:	3920 mm
SRI:	625
Tread depth:	46 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2070	2350	2635	2915	3200	3425	3615	3835
10H	1715	1990	2265	2495	2695	2875		
25	1770	2050	2330	2575	2775	2965		
30	1715	1990	2265	2495	2695	2875		
40		1895	2155	2375	2565	2740		
50		1820	2065	2280	2460	2625		
65			1970	2170	2345	2500		
70			1790	1975	2130	2275		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES