

540/65 R 28 142D TL TRAXION 65

EAN CODE: **8714692360510**
SKU CODE: **LB54652842DT6LA00**
ECE NUMBER: **E4-106R-003347**



Recommended rim width:	DW16L
Permitted rim width:	W16L/(D)W18L
Nominal Tyre Pressure:	160 kpa
Section Width:	540 mm
Outer Diameter:	1410 mm
Static Loaded Radius:	635 mm
Rolling Circumference:	4210 mm
SRI:	675
Tread depth:	46 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2215	2510	2820	3120	3425	3665	3865	4105
10H	1835	2130	2420	2670	2880	3045		
25	1890	2195	2495	2750	2970	3140		
30	1835	2130	2420	2670	2880	3045		
40		2030	2305	2540	2745	2900		
50		1945	2210	2440	2630	2785		
65			2105	2320	2505	2650		
70			1915	2115	2280	2410		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES