

540/65 R 30 150D TL TRAXION 65

EAN CODE: **8714692360534**

SKU CODE: **LB54653050DT6LA00**

ECE NUMBER: **E4-106R-033338**



Recommended rim width:	DW16L
Permitted rim width:	W16L/(D)W18L
Nominal Tyre Pressure:	240 kpa
Section Width:	540 mm
Outer Diameter:	1460 mm
Static Loaded Radius:	660 mm
Rolling Circumference:	4380 mm
SRI:	700
Tread depth:	46 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	2285	2590	2905	3215	3530	3780	3990	4235	4415	4620	4825	5025
10H	1895	2195	2495	2755	2975	3135	3355	3525	3670	3850		
25	1950	2265	2575	2840	3065	3230	3460	3630	3785	3970		
30	1895	2195	2495	2755	2975	3135	3355	3525	3670	3850		
40		2090	2380	2620	2830	2985	3195	3355	3495	3670		
50		2005	2280	2515	2715	2860	3065	3215	3355	3520		
65			2170	2395	2585	2725	2920	3065	3195	3350		
70			1975	2180	2350	2480	2655	2790	2905	3050		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.