

540/65 R 38 147D TL TRAXION 65

EAN CODE: **8714692360572**
 SKU CODE: **LB54653847DT6LA00**
 ECE NUMBER: **E4-106R-003351**



Recommended rim width:	DW16L
Permitted rim width:	W16L/(D)W18L
Nominal Tyre Pressure:	160 kpa
Section Width:	545 mm
Outer Diameter:	1685 mm
Static Loaded Radius:	770 mm
Rolling Circumference:	5020 mm
SRI:	800
Tread depth:	46 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2555	2895	3250	3595	3950	4225	4460	4735
10H	2120	2455	2790	3080	3325	3535		
25	2180	2530	2875	3175	3425	3645		
30	2120	2455	2790	3080	3325	3535		
40		2340	2660	2935	3165	3365		
50		2245	2550	2810	3035	3230		
65			2430	2680	2890	3075		
70			2210	2435	2630	2800		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.