

600/65 R 38 153D TL TRAXION 65

EAN CODE: **8714692360589**
 SKU CODE: **LB60653853DT6LA00**
 ECE NUMBER: **E4-106R-003352**



Recommended rim width:	DW18L
Permitted rim width:	W18L/DW20B
Nominal Tyre Pressure:	160 kpa
Section Width:	595 mm
Outer Diameter:	1750 mm
Static Loaded Radius:	790 mm
Rolling Circumference:	5210 mm
SRI:	825
Tread depth:	53 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2995	3400	3815	4220	4635	4960	5235	5555
10H	2485	2885	3275	3615	3900	4200		
25	2560	2970	3375	3725	4020	4325		
30	2485	2885	3275	3615	3900	4200		
40		2745	3120	3440	3715	3995		
50		2635	2990	3300	3560	3835		
65			2850	3145	3390	3650		
70			2595	2860	3085	3320		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES