

600/70 R 28 157D TL TRAXION XXL

EAN CODE: **8714692244629**
SKU CODE: **LB60702857DTXLA00**
ECE NUMBER: **E4-106R-000436**



Recommended rim width:	DW20B
Permitted rim width:	(D)W18L
Nominal Tyre Pressure:	240 kpa
Section Width:	610 mm
Outer Diameter:	1540 mm
Static Loaded Radius:	700 mm
Rolling Circumference:	4590 mm
SRI:	725
Tread depth:	51 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	2945	3340	3750	4150	4560	4885	5165	5475	5705	5900	6140	6190
10H	2445	2835	3225	3605	3875	4080	4330	4515	4675	4745		
25	2515	2920	3320	3715	3990	4205	4460	4650	4820	4890		
30	2445	2835	3225	3605	3875	4080	4330	4515	4675	4745		
40		2700	3070	3435	3690	3885	4120	4300	4450	4515		
50		2590	2945	3295	3535	3730	3950	4120	4270	4330		
65			2805	3135	3370	3550	3765	3925	4065	4125		
70			2550	2855	3065	3230	3425	3575	3700	3755		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.