

750/45 R 26.5 IMP 170D TL FLOTATION TRAC



EAN CODE: **8714692186721**
 SKU CODE: **LB75452670DFTLA00**
 ECE NUMBER: **E4-106R-000347**

Recommended rim width:	AG 24.00
Nominal Tyre Pressure:	400 kpa
Section Width:	745 mm
Outer Diameter:	1365 mm
Static Loaded Radius:	620 mm
Rolling Circumference:	4180 mm
SRI:	650
Tread depth:	25 mm

Speed (km/h)	Pressure (bar)								
	0,80	1,20	1,60	2,00	2,40	2,80	3,20	3,60	4,00
10	3595	4900	5990	7080	8075	8785	9490	10195	10800
25	3155	4305	5260	6215	7090	7710	8330	8950	9480
30	3015	4110	5025	5940	6775	7370	7960	8555	9060
40	2715	3705	4525	5350	6100	6635	7170	7705	8160
50	2415	3295	4025	4760	5430	5905	6380	6855	7260
65	1995	2725	3330	3935	4485	4880	5275	5665	6000
70	1815	2480	3030	3580	4085	4440	4800	5155	5460

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.