

# 280/85 R 24 130A8/B TL TRAXION 85 II

EAN CODE: **8714692350566**  
 SKU CODE: **LB288524308T8LA00**  
 ECE NUMBER: **E4-106R-002541**



Alternative size:	<b>11.2 R 24</b>
Recommended rim width:	<b>W10</b>
Permitted rim width:	<b>W9</b>
Nominal Tyre Pressure:	<b>400 kpa</b>
Section Width:	<b>295 mm</b>
Outer Diameter:	<b>1095 mm</b>
Static Loaded Radius:	<b>515 mm</b>
Rolling Circumference:	<b>3320 mm</b>
SRI:	<b>525</b>
Tread depth:	<b>38 mm</b>

Speed (km/h)	Pressure (bar)									
	0,80	1,20	1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40
10L	1165	1385	1610	1860	2005	2100	2265	2430	2520	
10H	925	1095	1300	1430	1500	1665	1800	1915	2035	
25	955	1135	1350	1480	1555	1730	1865	1990	2110	
30	925	1095	1300	1430	1500	1665	1800	1915	2035	
40		1025	1215	1335	1400	1555	1680	1790	1900	
50		1025	1215	1335	1400	1555	1680	1790	1900	

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.